ROCK MATTRESSES DESIGNED TO RESIST MOVEMENT IN HIGH-FLOW CONDITIONS

GEOFABRICS GEOMATTRESS ROCK MATTRESS - GALVANISED

TECHNICAL DATA SHEET

Geofabrics® Geomattress™ rock mattresses are constructed with double twisted steel wire mesh filled with rock to form thin, flexible cages designed to resist movement in high-flow conditions.

The structure is divided into cells which prevent displacement and enhance stability.

- · All wire used in the manufacture of Geomattress rock mattresses complies with EN 10223-3:2013 and has a tensile strength of 350 - 550 N/mm²
- · The steel wire used is Zn-10%Al coated
- · Proven to be over 50 per cent more effective than rip-rap in high shear stress conditions

GEOMATTRESSES GALVANISED COATED - SPECIFICATIONS

TEST	STANDARD	UNITS	VALUE		
Physical Properties					
Steel wire diameter	EN 10218-2	mm	2.00		
Selvedge wire diameter	EN 10218-2	mm	2.40		
Zn-10%Al Coating	EN 10244-2	Class	А		

SIZES				
Length (m)	Width (m)	Height (m)	No. of diaphragms	
6	2	0.17	5	
6	2	0.23	5	
6	2	0.30	5	


LACING

Lacing wire is used in the assembly of mattresses. The diameter of the steel wire shall be 2.2mm.

Zn-Al coated steel rings having the following specification can be used instead of lacing wire for mattress assembly:

- diameter: 3.00 mm
- tensile strength: >1720 MPa
- Pull-apart strength > 2.0 kN

Sizes and dimensions are nominal. Tolerance of ± 5% is permitted.



Visit **geofabrics.com.au** or call 1300 60 60 20 (AU) or **geofabrics.co.nz** or call 0800 60 60 20 (NZ)







