



GEOFABRICS CASE STUDY



MOISTURE-CONTROL GEOTEXTILE REINFORCES QUEEN STREET PAVEMENT

PRODUCTS USED

Mirafi® H2Rx Multifunctional Woven Geotextile

- Made from high tenacity polypropylene yarn, providing superior separation, mechanical stabilisation, and moisture management for road pavements and railway structures
- Separates and prevents the intermixing of subgrade soil and structural gravel layers
- Advanced wicking technology quickens moisture removal and drains moisture to prevent cracks, potholes and frost boils
- Equalises moisture content in expansive clay subgrades, preventing differential heaving and shrinkage that cause pavement stress
- High tensile modulus mechanically strengthens road pavement for longer design life

Megaflo® Green Socked Slotted Drain Pipe

- A wide, flat-shaped panel drainage system made from recycled HDPE and wrapped with Bidim® Green non-woven geotextile for quick and effective sub-surface drainage
- Up to 4.9 times faster water drainage compared to conventional 100mm round agi pipe due to its ability to effectively remove excess water with its increased in-take slot distribution
- Saves up to 50% installation compared to conventional 100mm round agi pipe
- Higher compressive strength under traffic loads due to its structural rigidity

MIRAFI® is a registered trademark of Solmax.

PROJECT DESCRIPTION

Livingstone Shire Council undertook a critical infrastructure upgrade on Queen Street, Yeppoon in Queensland, to address severe surface cracking caused by a soft, saturated subgrade.

The Council needed a solution that would reinforce the pavement and manage moisture effectively, drawing excess water away from the subgrade while also providing structural support. The goal was to improve the long-term performance of the road by preventing further cracking and minimising future maintenance.

OUR SOLUTION

After consultation with their Pavements Engineer, the Council selected Mirafi H2Rx multifunctional woven geotextile, an innovative solution providing separation, filtration, reinforcement, and moisture management.


The construction team removed the existing pavement and stabilised the subgrade through excavation and replacement with basecourse material, and installed Megaflo Green socked slotted drain pipe. Mirafi H2Rx geotextile was laid with a tile overlap and embedded into the Megaflo drain pipe, creating a direct drainage pathway to effectively manage moisture levels.

Mirafi H2Rx geotextile was deployed across 3,600 m² of pavement, delivering critical reinforcement and moisture control. Its wicking properties efficiently removed excess moisture, preventing subgrade saturation and surface cracking. The material also provided essential separation and structural support, enhancing pavement durability.

A staged construction approach ensured minimal disruption, and the successful outcome demonstrated the geotextile's dual role in mechanical and moisture stabilisation.

3,600 m²
pavement reinforced

Effective moisture control



Visit **geofabrics.co** or call 1300 60 60 20 (AU)
or **geofabrics.co.nz** or call 0800 60 60 20 (NZ)

GEOFABRICS
Sustainable solutions

IMPORTANT NOTICE - DISCLAIMER - The information contained in this brochure is general in nature. In particular the content of this brochure does not take account of specific conditions that may be present at your site. For full disclaimer and further information regarding installation visit geofabrics.co/disclaimer
© Copyright held by Geofabrics Australasia Pty Ltd. All rights are reserved and no part of this publication may be copied without prior permission. Published January 2026.

